



STRONG ALUMINUM
FRAME



ERGONOMIC
HANDLE



SECURE
LOCK



SMOOTH ROLLERS
FOR EASY GLIDE



MULTI-TRACK
OPTIONS



UNIT: INCH

INSTALLATION DETAIL

ROUGH OPENING:
Door Dimensions will be exactly your door size with a frame.
Recommended rough opening is between 3/4" (19mm) – 1" (25mm)
larger than the Door width and height.
Ensure that the rough opening is plumb, level and square,
and the walls in the opening are not twisted.



75 SERIES SLIDING DOORS SPECIFICATION



DURABLE
ALUMINUM



NOISE
REDUCTION



THERMAL
INSULATION



WEATHER
RESISTANT



SECURE
LOCKING



EASY
INSTALLATION

HORIZONTAL SECTION



PRODUCT FEATURES

- Heavy-duty aluminum alloy frame for strength and durability
- Smooth and quiet sliding operation
- Multi-track system for flexible configurations
- Tempered double glass for safety and energy efficiency
- Weather-resistant design to withstand all climates
- Secure multi-point locking system
- Low maintenance and easy to clean
- Multiple color and finish options available
- Ideal for residential and commercial applications

GLASS DETAILS

- DOUBLE TEMPERED GLASS
- EACH PANE 5MM GLASS
- E GLASS 100% BLOCK UV
- FILLED WITH ARGON GAS
- 5mm GLASS PANE + 27mm ARGON GAS + 5MM GLASS PANE



PROJECT

DOOR TYPE

75 Series Sliding Doors Specification

NOTES

1. All dimensions are in inch & inches
2. All dimensions are to be checked on site.
3. Any discrepancy between the architectural drawings and other drawings relevant for construction should be notified before commencement.

