




STRONG ALUMINUM FRAME SECURE LOCK ERGONOMIC HANDLE SMOOTH SLIDING TRACK WITH DRAINAGE

INSTALLATION DETAIL

ROUGH OPENING:

Door Dimensions will be exactly your door size with a frame.
Recommended rough opening is between 3/4" (19mm) – 1" (25mm) larger than the Door width and height.
Ensure that the rough opening is plumb, level and square, and the walls in the opening are not twisted.



UNIT: INCH

A1 DOORS & WINDOWS

75 SERIES SLIDING WINDOWS SPECIFICATION



DURABLE
ALUMINUM



NOISE
REDUCTION



THERMAL
INSULATION



WEATHER
RESISTANT




SECURE
LOCKING



EASY
INSTALLATION

HORIZONTAL SECTION



PRODUCT FEATURES

- Durable aluminum alloy frame for long-lasting performance
- Smooth and quiet sliding operation
- Tempered double glass for safety and energy efficiency
- Weather-resistant design to withstand all climates
- Secure multi-point locking system
- Easy to operate and low maintenance
- Ideal for residential and commercial applications
- Multiple color and finish options available

GLASS DETAILS

- DOUBLE TEMPERED GLASS
- EACH PANE 5MM GLASS
- E GLASS 100% BLOCK UV
- FILLED WITH ARGON GAS
- 5mm GLASS PANE + 27mm ARGON GAS + 5MM GLASS PANE

A1 DOORS & WINDOWS

PROJECT

WINDOW TYPE

75 Series Sliding Windows Specification

NOTES

1. All dimensions are in inch & inches
2. All dimensions are to be checked on site.
3. Any discrepancy between the architectural drawings and other drawings relevant for construction should be notified before commencement.



www.doorandwindow.store

(747) 306-6842



info@doorandwindow.store